

Phottix® Kali 600

LED Light

Phottix® Kali 600



PH81440 Phottix Kali600 LED Light

The Kali600 model – a larger studio-style LED Panel for video and general studio and location photography.

Features:

Excellent color rendering - CRI 95+

Digital Power Control: 10% - 100%

Digital Color Control: 3300K – 5600K

Uses 2 Sony-compatible batteries or AC Adapter



The Phottix Kali600 features a maximum brightness of 3000Lux (36W). Being both mains and battery powered it can be used in the studio or on-location. The Kali600 offers power and color temperature control – via the panel as well as a wireless radio remote. Barndoors, white diffuser panel and AC Adapter are included.



Removable Barndoors



Removable White Diffuser Panel



2.4G wireless remote control

Kali600 LED Technical Specs:

SKUs / Model:	PH81440 Phottix Kali600 LED Light
Color Rendering Index (CRI):	> 95
Color Temperature (adjustable):	3300K~5600K
Maximum Brightness:	3000Lux @ 1m
Power:	36W @ full power
Battery:	2 x Compatible NP Series (NP-F550 / 750 / 960)
Battery Life:	2 x NP-F550 (7.4V 2000mAh) 90min
5600K at Max Power	2 x NP-F750 (7.4V 4600mAh) 240min
	2 x NP-F970 (7.4V 6600mAh) 3600min
Remote Control Range:	>50m
Dimensions:	242mm x 191mm x 42mm (9.5" x 7.5" x 1.7")
Weight:	1340g (not include battery / barndoor)
AC/DC adaptor operation voltage:	100-240VAC